

DOUBLE SIDED PET TAPE

(DSE8980G)

TQPBOND®



Product Code:DSE8980G

This double sided tape uses PET as the carrier with acrylic adhesive evenly coated on both sides and then lined with release paper. Mainly suitable for the bonding of labels, LCD backlight, LCD panel and other metal frames and components in digital electronics.

Description

Features:

- Flexible carrier material, strong adhesive strength for curve, rough surfaces and other similar objects
- Excellent heat resistance and moisture resistance property
- The release liner may be customized upon customer's needs, such as brown glassine paper, white glassine paper and release film, etc.

Typical Applications:

- Mainly suitable for the bonding of labels, LCD backlight, LCD panel and other metal frames and components in digital electronics.

Available Colors:

clear

Available Sizes:

Width: 6mm--1240mm

Length: up to 50m

jumbo rolls up to 100m

Physical Properties:

Testing Items	Value
Backing	PET
Adhesive	Solvent based acrylic
Tape Thickness	155micron(6.2mil/0.155mm)
Tack	14# ≤120mm (GB/T4852-2002)
Adhesion to Steel	≥10N/25mm (GB/T2792-1998)
Holding Power	≥ 24 hour (GB/T4851-1998)
Heat Resistance	120 °C

Note: The above technical data is obtained from tests and does not represent a guarantee of product performance. Individual rolls may vary slightly from these averages.